R33NV 2/2024







# R33NV/R33LP-NV

Field-Proven Rotator® Technology

25-65 PSI (1.75-4.5 BAR) 39-52' RAD. (12-16 M) 2.8-11.0 GPM (638-2524 LPH)





# **ROTATOR® TECHNOLOGY**

# **BETTER THAN BRASS**

R33NV & R33LP-NV Rotators continue the standard of performance and value from Nelson Irrigation and Rotator® Technology in a 3/4" sprinkler. The new 3NV incorporates a multi-function nozzle for nozzle flush, line flush, shutoff - all without removing the nozzle.

- HIGH UNIFORMITY
- **EASY TO CLEAN**
- **EASY TO REPAIR**
- **LONG WEAR LIFE**
- NO RISER VIBRATION
- NO SEALS UNDER PRESSURE
- REPLACE IMPACT SPRINKLERS
  - **REDUCE THEFT**

Rotator® sprinklers on blueberries in the Willamette Valley, Oregon.



The Road Guard (#11363) easily snaps on to convert the R33-NV and R33LP-NV to part-circle operation. Best edge-of-field solution to prevent watering on adjacent roads and fields.

The Cap Assembly Removal Tool (#13930) makes alterations a snap.












SYSTEM TYPES INCLUDE: Portable aluminum, polyethylene, and PVC pipe; wheel lines and permanent solid set systems.

APPLICATIONS INCLUDE: Irrigation of all types of crops including forage crops, vegetables, grain and pastures. Overhead irrigation, cooling and environmental control for nursery crops, tree, vine, small fruit and berries. Also suitable for revegetation, mining and other specialty uses.



The R33-NV is available in a low pressure model (the R33LP-NV). This is designated by a green cap.

## R33-NV & R33LP-NV PARTS

| PLATE                         | NOZZLE                            | LEGACY 33TN<br>NOZZLE/PLATE<br>COLORS | BODY<br>ASSY | R33-NV<br>CAP/PLATE<br>ASSEMBLY | R33LP-NV<br>CAP/PLATE<br>ASSEMBLY | R33-NV FULL<br>ASSEMBLY                        | R33LP-NV<br>FULL ASSEMBLY                       |  |
|-------------------------------|-----------------------------------|---------------------------------------|--------------|---------------------------------|-----------------------------------|--|---|--|
| #18<br>Gray<br>2965-018       | Gray<br>(9/64")<br>12035-018      | Gold                                  | 14010-018    | 13422-018                       | 13422-118                         | 13373 -018<br>(Black Diffuser,<br>Gray Motor)  | 13373 -118<br>(Purple Diffuser,<br>Green Motor) |  |
| #20<br>Turquoise<br>12965-020 | Turquoise<br>(5/32")<br>12035-020 | Brown                                 | 14010-020    | 13422-020                       | 13422-120                         | 13373 -020<br>(Black Diffuser,<br>Gray Motor)  | 13373 -120<br>(Purple Diffuser,<br>Green Motor) |  |
| #22<br>Yellow<br>12965-022    | Yellow<br>(11/64")<br>2035-022    | Gray                                  | 14010-022    | 13422-022                       | 13422-122                         | 13373 -022<br>(Black Diffuser,<br>Ivory Motor) | 13373 -122<br>(Green Diffuser,<br>Purple Motor) |  |
| #24<br>Red<br>12965-024       | Red<br>(3/16")<br>2035-024        | Green                                 | 14010-024    | 13422-024                       | 13422-124                         | 13373 -024<br>(Black Diffuser,<br>Ivory Motor) | 13373 -124<br>(Green Diffuser,<br>Purple Motor) |  |
| #26<br>White<br>12965-026     | White<br>(13/64")<br>2035-026     | Maroon                                | 14010-026    | 13422-026                       | 13422-126                         | 13373 -026<br>(Gray Diffuser,<br>Ivory Motor)  | 13373 -126<br>(Green Diffuser,<br>Purple Motor) |  |
| #28<br>Blue<br>12965-028      | Blue<br>(7/32")<br>12035-028      | Blue                                  | 14010-028    | 13422-028                       | 13422-128                         | 13373 -028<br>(Gray Diffuser,<br>Ivory Motor)  | 13373 -128<br>(Green Diffuser,<br>Purple Motor) |  |

The R33NV and R33LP-NV motors, plates, and diffusers have been updated to improve reliability and uniformity. The components (motor, diffuser, plate) of cap assemblies from old versions and new versions should not be mixed. WE RECOMMEND THAT THE R33-NV & R33LP-NV BE STOCKED AND PURCHASED AS A FULL ASSEMBLY. PLEASE ORDER ALL OTHER PARTS FOR THE PURPOSE OF REPAIRS ONLY.



# R33NV & R33LP-NV

## PART NUMBERS & PERFORMANCE

13373-XXX

Standard NV = 0 Low Pressure (LP-NV) = 1

PLATE/NOZZLE (Gray = 18, Turquoise = 20, Yellow = 22, Red = 24, White = 26 Blue = 28

### **U.S. UNITS (FLOW IN GPM)**

#### METRIC UNITS (FLOW IN LPH)

| PLATE & 3NV<br>NOZZLE<br>COMBO | MODEL & RADIUS IN FEET | PSI |     |     |     |      |      |      | MODEL & | BAR  |                       |      |      |      |      |      |       |      |      |
|--------------------------------|------------------------|-----|-----|-----|-----|------|------|------|---------|------|-----------------------|------|------|------|------|------|-------|------|------|
|                                |                        | 25  | 30  | 35  | 40  | 45   | 50   | 55   | 60      | 65   | METERS                | 1.75 | 2.0  | 2.5  | 2.75 | 3.0  | 3.5   | 4.0  | 4.5  |
| #18 Gray<br>(9/64")            | R33LP<br>39-42'        | 2.8 | 3.0 | 3.3 | 3.5 | 3.7* | 3.9* | -    | _       | _    | R33LP<br>12.0-13.0 m  | 638  | 671  | 751  | 787  | 822  | 900*  |      | _    |
|                                | R33<br>43'             | _   |     | _   | 3.5 | 3.7  | 3.9  | 4.1  | 4.3     | 4.5  | R33<br>13.0 m         | _    | _    | _    | 787  | 822  | 900   | 963  | 1021 |
| #20 (5/32")<br>Turquoise       | R33LP<br>40-42'        | 3.5 | 3.8 | 4.1 | 4.4 | 4.7* | 4.98 | -    | _       | _    | R33LP<br>12.0-12.75 m | 799  | 842  | 942  | 988  | 1032 | 1129* |      | _    |
|                                | R33<br>44-45'          | _   |     | _   | 4.4 | 4.7  | 4.9  | 5.1  | 5.4     | 5.6  | R33<br>13.5-13.75 m   | _    | _    | _    | 988  | 1032 | 1129  | 1207 | 1280 |
| #22 Yellow<br>(11/64")         | R33LP<br>42-45'        | 4.2 | 4.6 | 4.9 | 5.3 | 5.6  | 5.9  | -    | _       |      | R33LP<br>12.75-13.75  | 961  | 1010 | 1130 | 1186 | 1238 | 1357  |      | _    |
|                                | R33<br>46-47'          | _   | _   | _   | 5.3 | 5.6  | 5.9  | 6.2  | 6.5     | 6.7  | R33<br>14.0-14.25 m   | _    | _    | _    | 1186 | 1238 | 1357  | 1451 | 1539 |
| #24 Red<br>(3/16")             | R33LP<br>43-46'        | 5.0 | 5.5 | 5.9 | 6.3 | 6.7  | 7.1  | -    | _       | _    | R33LP<br>13.0-14.0    | 1149 | 1212 | 1354 | 1420 | 1483 | 1627  |      | _    |
|                                | R33<br>47-50'          | _   | _   | _   | 6.3 | 6.7  | 7.1  | 7.4  | 7.7     | 8.0  | 8.4                   | _    | _    | _    | 1420 | 1483 | 1627  | 1739 | 1844 |
| #26 White (13/64")             | R33LP<br>43-47'        | 5.9 | 6.4 | 6.9 | 7.4 | 7.8  | 8.3  | -    | _       | _    | R33LP<br>13.25-14.5   | 1348 | 1421 | 1587 | 1665 | 1739 | 1907  | _    | _    |
|                                | R33<br>49-50'          | _   | _   | _   | 7.4 | 7.8  | 8.3  | 8.7  | 9.1     | 9.4  | R33<br>15.0-15.25     | _    | _    | _    | 1665 | 1739 | 1907  | 2039 | 2163 |
| #28 Blue<br>(7/32")            | R33LP<br>45-47'        | 6.8 | 7.5 | 8.1 | 8.6 | 9.2  | 9.7  | _    | _       |      | R33LP<br>13.75-14.25  | 1574 | 1658 | 1854 | 1944 | 2031 | 2226  |      | _    |
|                                | R33<br>51-52'          | _   |     |     | 8.6 | 9.2  | 9.7  | 10.1 | 10.6    | 11.0 | R33<br>15.5-16.0      |      | _    | _    | 1944 | 2031 | 2226  | 2379 | 2524 |

\*Flow and radius data highlighted in gray for a particular plate/nozzle combination indicates that the pressure is outside the recommended range for uniformity-sensitive applications. The absence of data for a particular model/plate/nozzle combination indicates the pressure is outside the recommended range. Measured indoors in no wind with plates mounted 18 inches (0.46 meters) above collection cups. GPM = gallons per minute. LPH = liters per hour.



Nelson Irrigation Corporation 848 Airport Road Walla Walla, WA 99362, USA Tel: +1 509-525-7660 nelsonirrigation.com info@nelsonirrigation.com

Nelson Australia 20 Macadam Street Seventeen Mile Rocks, QLD 4073 Tel: +61 7 3715 8555 nelsonirrigation.com.au info@nelsonirrigation.com.au WARRANTY AND DISCLAIMER: Nelson R33-NV/R33LP-NV Rotator® Sprinklers are warranted for one year from the date of the original sale to be free of defective material and workmanship when used within the working specifications for which the products were designed and under normal use and service. The manufacturer assumes no responsibility for installation, removal or unauthorized repair of defective parts and the manufacturer will not be liable for any crop or other consequential damages resulting from any defects or breach of warranty. THIS WARRANTY IS EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSES AND OF ALL OTHER OBLIGATIONS OR LIABILITIES OF MANUFACTURER. No agent, employee or representative of the manufacturer has authority to waive, alter or add to the provisions of this warranty nor to make any representations or warranty not contained herein.